

Eaton 170M4466

Catalog Number: 170M4466

Fuse-link, high speed, 630 A, AC 690 V, size 1, aR, IEC, UL, type K indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M4466
	UPC
	051712258968
EAN	Product Length/Depth
5027590520119	70 mm
Product Height	Product Width
51 mm	51 mm
Product Weight	Warranty
397 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

630 A

Breaking capacity

200 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1

Rated voltage AC

690 V

Center-to-center distance of connections

51.1 mm

Current type

AC

Mounting dimension

M8

Class

Class aR

Clearing (I2T)

350000 at 660 V

Watt losses

80 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

170M4466-Eaton Bussmann series high speed square body fuse

Compliance information

CE Fuse-links for the protection of semiconductor devices, Size 1 up to 900A

UKCA Fuse-links for the protection of semiconductor devices, Size 1 up to 900A

Pre arc (I2T)

52000

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type K Indicator for micro

Construction size

1

Mounting method

Flush

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

Flush end

BKN/Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)