

Fuse-link, high speed, 250 A, AC 690 V, size 1, 53 x 69 x 51 mm, aR, IEC, single indicator



170M4559

Similar to illustration

General specifications		
Product name	Ea	aton Bussmann series high speed square body fuse
Part no.	17	70M4559
EAN	50	27590453486
Product Length/Depth	73	3 millimetre
Product height	52	? millimetre
Product width	170	70 millimetre
Product weight	153	i3 gram
Compliances		oHS Compliant E Marked
Certifications		C Rated L Recognized
Product Tradename	No	one
Product Type	Hiç	igh speed square body fuse
Product Sub Type	No	one
Electrical data		
Amperage Rating	25	60 A
Voltage rating	69	00 V
Interrupt rating	20	00 kAIC
Class	Cla	ass aR
Clearing (I2T)	210	000 at 660 V
Product specifications		
Application	se	emiconductor protection
Fuse type	Flu	ush end
Fuse indicator	Се	entre fuse status indicator
Fuse size	1	

Technical data ETIM 9.0

Icommodi data Ellin 3.0			
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical inst	allation, device / Safe	ety fuse ir	nserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])
Fuse system according to IEC 60269			IEC 60269-4 flush end connections type A
Fuse construction type according to IEC 60269			1
Type of current			AC
Rated voltage AC	,	V	690
Rated voltage DC	,	V	
Rated current		Α	250
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	200
Colour code			None
Type of fuse status indicator			Centre fuse status indicator
Power loss at rated current	,	W	55
Mounting holes			Other
Centre-to-centre distance of connections		mm	51