

Eaton 170M4813

Catalog Number: 170M4813

Eaton Bussmann series high speed square body fuse,200A,125 kAIC,Class aR,Blade end X Din 43-620 blade end,DIN 43 620,Standard,Clearing at 1000V: 40500,square body with centre-bolted tags (slotted),Top fuse status indicator,5600,40W



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M4813
	Model Code
	FUSE 200A 1000V 00/80 AR
EAN	UPC
5027590454285	051712679268
Product Length/Depth	Product Height
233 mm	66 mm
Product Width	Product Weight
140 mm	232 g
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

200 A

Breaking capacity

125 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

1000 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

40500 at 1000 V

Watt losses

40 W

Fuse shape

Square body, slotted center bolted tags

Resources

Compliance information

UKCA Fuse-links for the protection of semiconductor devices, sz00 up to 250A

CE Fuse-links for the protection of semiconductor devices, sz00 up to 250A

Pre arc (I2T)

5600

Color

None

Interrupt rating

125 kAIC

Connection

Blade end x Din 43-620 blade end

Construction size

00

Packaging type

Standard

Voltage rating

1000 V (IEC)

Fuse type

DIN 43653

00/80 Visual indicator

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)