

Eaton 170M4834

Catalog Number: 170M4834

Fuse-link, high speed, 250 A, AC 1000 V, size 00, 30 x 47 x 98 mm, aR, DIN, IEC, single indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M4834
	UPC
	051712798518
EAN	Product Length/Depth
5027590454827	233 mm
Product Height	Product Width
66 mm	140 mm
Product Weight	Warranty
248 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

250 A

Breaking capacity

125 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

1000 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

74000 at 1000 V

Watt losses

48 W

Fuse shape

Square body, slotted center bolted tags

Resources

Catalogs

170M4834-Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Compliance information

CE Fuse-links for the protection of semiconductor devices, sz00 up to 250A

UKCA Fuse-links for the protection of semiconductor devices, sz00 up to 250A

Pre arc (I2T)

10000

Color

None

Interrupt rating

125 kAIC

Connection

Blade end x Din 43-620 blade end

Construction size

00

Packaging type

Standard

Voltage rating

1000 V (IEC)

Fuse type

DIN 43653

00TN/80 Type T Indicator for micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia