

Eaton 170M4867D

Catalog Number: 170M4867D

Fuse-link, high speed, 700 A, AC 690 V, DIN 1, aR, DIN, IEC, dual indicator, live gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M4867D
	UPC
	051712334143
EAN	Product Length/Depth
5027590454889	135 mm
Product Height	Product Width
64 mm	40 mm
Product Weight	Warranty
426.8333333 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

700 A

Breaking capacity

200 kA

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1

Rated voltage AC

690 V

Current type

AC

Class

Class aR

Clearing (I₂T)

495000 at 660 V

Watt losses

39 W

Fuse shape

Square body, knife blade contacts

Pre arc (I₂T)

69500

Color

None

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[UKCA NH-style, high-speed dual indicator fuselinks](#)

[CE NH-style, high-speed dual indicator fuselinks](#)

Technical data sheets

[720101 DIN 43620 690V Dual ind](#)

Interrupt rating

200 kAIC

Fitted with:

Dual indicator

Connection

Din 43-620 blade end x Din 43-620 blade end

Construction size

1

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43620

Bladed

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)