# Eaton 170M5140

### Catalog Number: 170M5140

Eaton Bussmann series high speed square body fuse, 315A, 100 kAIC, Class aR, DIN 43 620, Standard, Clearing at 1000V: 77500, Clearing at 1250V: 105000, square body with centre-bolted tags (slotted), Top fuse status indicator, 75W





Eaton Bussmann series high speed

square body fuse

Catalog Number

170M5140

Model Code

FUSE 315A 1250V 2/110 AR CU

**INDICATOR** 

**UPC** 

**EAN** 051712260183 5027590455817

Product Length/Depth **Product Height** 

284 mm 67 mm

**Product Width Product Weight** 

175 mm 634 g

Compliances Certifications **CE Marked UL** Recognized **RoHS Compliant IEC Rated** 





### defaultTaxonomyAttributeLabel

## Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 315 A Breaking capacity 100 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No **Utilization category** aR (accompanied semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 1250 V Center-to-center distance of connections 108 mm Current type AC Mounting dimension M10 Class Class aR Clearing (I2T) 77500 at 1000 V, 105000 at 1250 V

Watt losses 75 W

Fuse shape

Square body, slotted center bolted tags

### Resources

#### Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-enus.pdf

### Pre arc (I2T)

13000

Color

None

Interrupt rating

100 kAIC

Construction size

2

Mounting method

DIN 43 620

Packaging type

Standard

Voltage rating

1250 V (IEC), 1300 V (UL)

Fuse type

DIN 43653

/110 Visual indicator

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia