

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

315 A

Breaking capacity

100 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

2

Rated voltage AC

1250 V

Center-to-center distance of connections

108 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

77500 at 1000 V, 105000 at 1250 V

Watt losses

75 W

Fuse shape

Square body, slotted center bolted tags

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Pre arc (I2T)

13000

Color

None

Interrupt rating

100 kAIC

Construction size

2

Packaging type

Standard

Voltage rating

1250 V (IEC), 1300 V (UL)

Fuse type

DIN 43653

KN/110 Type K Indicator for Micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia