

Eaton 170M5262

Catalog Number: 170M5262

Fuse-link, high speed, 630 A, AC 690 V, DIN 2, 61 x 77 x 138 mm, aR, DIN, IEC, single indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M5262
	Model Code
	FUSE 630A 690V 2KN/110 AR UC
UPC	EAN
051712260794	5027590456494
Product Length/Depth	Product Height
286 mm	66 mm
Product Width	Product Weight
165 mm	641 g
Warranty	Compliances
Not Applicable	CE Marked RoHS Compliant
Certifications	
UL Recognized IEC Rated	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

630 A

Breaking capacity

200 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

2

Rated voltage AC

690 V

Center-to-center distance of connections

108 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

405000 at 660 V

Watt losses

90 W

Clearing loss

80

Resources

Catalogs

170M5262-Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Technical data sheets

720014 DIN 43653 690V

Fuse shape

Square body, slotted center bolted tags

Pre arc (I2T)

41000

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

2

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

KN/110 Type K Indicator for Micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)