

Eaton 170M5408

Catalog Number: 170M5408

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 400 A, 200 kAIC, Top fuse status indicator, Fuse, Class aR, Flush

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M5408
	EAN
	5027590456982
UPC	Product Length/Depth
051712261135	168 mm
Product Height	Product Width
80 mm	124 mm
Product Weight	Compliances
308.5 g	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	



defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

400 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

2

Rated voltage AC

690 V

Center-to-center distance of connections

50.4 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

74000 at 660 V

Watt losses

65 W

Fuse shape

Square body, flush end contacts

Resources

Compliance information

[CE Fuse-links for the protection of semiconductor devices, Size 2](#)

[UKCA Fuse-links for the protection of semiconductor devices, Size 2](#)

Pre arc (I2T)

11000

Color

None

Interrupt rating

200 kAIC

Construction size

2

Mounting method

Flush

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

Flush end

B/Visual indicator

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia