Eaton 170M5415

Catalog Number: 170M5415

Fuse-link, high speed, 900 A, AC 690 V, size 2, 61 x 77 x 51 mm, aR, IEC, UL, single indicator

General specifications

Product Name

Eaton Bussmann series high speed

square body fuse

Catalog Number

170M5415

UPC

051712261203

EAN

5027590457064

Product Length/Depth

168 mm

Product Height

80 mm

Product Width

124 mm

Product Weight

Warranty

Not Applicable

754 g

Certifications

Compliances **CE Marked**

IEC Rated

RoHS Compliant

UL Recognized



default Taxonomy Attribute LabelType Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 900 A Breaking capacity 200 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 690 V Center-to-center distance of connections 50.4 mm Current type AC Mounting dimension M10 Class Class aR Clearing (I2T) 840000 at 660 V Watt losses

110 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-

Bussmann series complete full line catalog no. 1007

170M5415~Eaton Bussmann series high speed square body fuse

Compliance information

UKCA Fuse-links for the protection of semiconductor devices, Size 2

CE Fuse-links for the protection of semiconductor devices, Size 2

Pre arc (I2T)

125000

Color

None

Interrupt rating

200 kAIC

Construction size

2

Mounting method

Flush

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

Flush end

B/Visual indicator

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia