# Eaton 170M5446

### Catalog Number: 170M5446

Fuse-link, high speed, 630 A, AC 1250 V, size 2, 61 x 77 x 81 mm, aR, IEC, UL, single indicator

#### General specifications



Eaton Bussmann series high speed square body fuse

UPC

051712261326

Product Length/Depth

92 mm

**Product Width** 

163 mm

Warranty

Not Applicable

Certifications

IEC Rated
UL Recognized

Catalog Number

170M5446

Model Code

FUSE 630A 1250V 2BKN/80 AR CU

**EAN** 

5027590457194

**Product Height** 

60 mm

**Product Weight** 

818 g

Compliances

CE Marked

**RoHS Compliant** 





#### default Taxonomy Attribute Label

## Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 630 A Breaking capacity 100 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 1250 V Center-to-center distance of connections 80.3 mm Current type AC Mounting dimension M10 Class Class aR Clearing (I2T) 575000 at 1000 V, 730000 at 1250 V Watt losses 110 W

Fuse shape

Square body, flush end contacts

#### Resources

#### Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-

Bussmann series complete full line catalog no. 1007

#### Pre arc (I2T)

115000

#### Color

None

#### Interrupt rating

100 kAIC

#### Fitted with:

Type K Indicator for micro

#### Construction size

2

#### Mounting method

Flush

#### Packaging type

Standard

#### Voltage rating

1250 V (IEC), 1300 V (UL)

#### Fuse type

Flush end

BKN/80 Type K Indicator for Micro

#### Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia