F.T.N

Eaton 170M5612

Catalog Number: 170M5612

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 630A, 200 kAIC, None, Fuse, Blade end X blade end, Class aR

General specifications



Eaton Bussmann series high speed

square body fuse

UPC

051712261852

Product Length/Depth

135 mm

Product Width

59 mm

Warranty

Not Applicable

Certifications

IEC Rated

UL Recognized

Catalog Number

170M5612

Model Code

FUSE 630A 690V 2FU/90 AR UC

EAN

5027590457880

Product Height

59 mm

Product Weight

281 g

Compliances

CE Marked

RoHS Compliant



default Taxonomy Attribute Label

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 630 A Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 2 Rated voltage AC 690 V Center-to-center distance of connections 90.9 mm Current type AC Mounting dimension M12 Class Class aR Clearing (I2T) 275000 at 660 V Watt losses 90 W Fuse shape

Square body, center bolted tags

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

170M5612~Eaton Bussmann series high speed square body fuse

Pre arc (I2T)

41000

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

2

Packaging type

Standard

Voltage rating

690 V

Fuse type

US Style

FU/Without indicator

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia