Eaton 170M5668

Catalog Number: 170M5668

Fuse-link, high speed, 1250 A, AC 600 V, size 2, 61 x 77 x 135 mm, aR, IEC, UL, single indicator, 90 mm fixing centres

General specifications

Product Name

Eaton Bussmann series high speed square body fuse

UPC 051712262071

Product Length/Depth 286 mm

Product Width 165 mm

Warranty Not Applicable

Certifications

IEC Rated UL Recognized Catalog Number 170M5668

Model Code FUSE 1250A 600V 2FKE/90 AR UC

EAN 5027590458184

Product Height 66 mm

Product Weight 318 g

Compliances CE Marked RoHS Compliant



Photo is representative



defaultTaxonomyAttributeLabel

Туре

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

1250 A

Breaking capacity

200 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

2

Rated voltage AC

600 V

Center-to-center distance of connections

90.3 mm

Current type

AC

Mounting dimension

M12

Class

Class aR

Clearing (I2T)

2400000 at 660 V

Watt losses

120 W

Fuse shape

Square body, center bolted tags

Resources

Catalogs

170M5668~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Pre arc (I2T)

365000

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type K Indicator for micro

Connection

Blade end x blade end

Construction size

2

Packaging type

Standard

Voltage rating

600 V

Fuse type

US Style FKE/Type K indicator for micro Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia