

# Eaton 170M5957

Catalog Number: 170M5957

Fuse-link, high speed, 500 A, AC 1000 V, size 2, 59 x 77 x 75 mm, aR, IEC, UL, type K indicator

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed square body fuse	170M5957
	<b>UPC</b>
	051712602235
<b>EAN</b>	<b>Product Length/Depth</b>
5027590461290	168 mm
<b>Product Height</b>	<b>Product Width</b>
80 mm	124 mm
<b>Product Weight</b>	<b>Warranty</b>
751.25 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

### Amperage Rating

500 A

### Breaking capacity

125 kA

### Fuse indicator

Centre fuse status indicator

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC

### Fuse size

2

### Rated voltage AC

1000 V

### Center-to-center distance of connections

74.3 mm

### Current type

AC

### Mounting dimension

M10

### Class

Class aR

### Clearing (I<sup>2</sup>T)

295000 at 1000 V

### Watt losses

95 W

### Fuse shape

Square body, flush end contacts

## Resources

### Catalogs

Bussmann series complete full line catalog no. 1007

### Compliance information

UKCA HS Size 2, rated 1000 Vac

CE HS Size 2, rated 1000 Vac

Pre arc (I2T)

49500

Color

None

Interrupt rating

125 kAIC

Fitted with:

Type K Indicator for micro

Construction size

2

Mounting method

Flush

Packaging type

Standard

Voltage rating

1000 V (IEC)

Fuse type

Flush end

BKN/Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)