

Eaton 170M5959

Catalog Number: 170M5959

Fuse-link, high speed, 630 A, AC 1000 V, size 2, 59 x 77 x 75 mm, aR, IEC, UL, single indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M5959
	Model Code
	FUSE 630A 1000V 2BKN/75 AR UR
UPC	EAN
051712531528	5027590461313
Product Length/Depth	Product Height
168 mm	80 mm
Product Width	Product Weight
124 mm	767.25 g
Compliances	Certifications
CE	IEC 60269-4
RoHS Compliant	UL
EAC	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

630 A

Breaking capacity

125 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

2

Rated voltage AC

1000 V

Center-to-center distance of connections

74.3 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Watt losses

110 W

Fuse shape

Square body, flush end contacts

Color

None

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

Compliance information

[CE HS Size 2, rated 1000 Vac](#)

[UKCA HS Size 2, rated 1000 Vac](#)

Interrupt rating

125 kAIC

Fitted with:

Type K Indicator for micro

Construction size

2

Mounting method

Flush

Packaging type

Standard

Voltage rating

1000 V (IEC)

Fuse type

Flush end

BKN/Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)