

Eaton 170M6020

Catalog Number: 170M6020

Fuse-link, high speed, 1800 A, AC 600 V, DIN 3, 76 x 76 x 109 mm, aR, DIN, IEC, single indicator

General specifications



Product Name

Eaton Bussmann series high speed square body fuse

Catalog Number

170M6020

Model Code

FUSE 1800A 600V 3/80 AR UR INDICATOR

EAN

5996516017357

UPC

051712792295

Product Length/Depth

168 mm

Product Height

76 mm

Product Width

95 mm

Product Weight

1186 g

Compliances

CE Marked
RoHS Compliant

Certifications

UL Recognized
IEC Rated

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

1800 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

3

Rated voltage AC

600 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

5250000 at 660 V

Watt losses

165 W

Clearing loss

165

Resources

Compliance information

UKCA Fuse-links for the protection of semiconductor devices, Size 3

CE Fuse-links for the protection of semiconductor devices, Size 3

Technical data sheets

720014 DIN 43653 690V

Fuse shape

Square body, slotted center bolted tags

Pre arc (I2T)

880000

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

3

Packaging type

Standard

Voltage rating

600 Vac

Fuse type

DIN 43653

/80 Visual indicator

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)