

Eaton 170M6080

Catalog Number: 170M6080

Fuse-link, high speed, 350 A, AC 690 V, DIN 3, 75 x 89 x 150 mm, gR, DIN, IEC, single indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M6080
	Model Code
	FUSE 350A 690V DIN 3 GR
EAN	Product Length/Depth
5996516017586	168 mm
Product Height	Product Width
76 mm	95 mm
Product Weight	Compliances
1475 g	CE
	RoHS Compliant
	EAC
Certifications	
IEC 60269-4	
DIN 43620	

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

350 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

3

Rated voltage AC

690 V

Current type

AC

Class

Class gR

Watt losses

55 W

Fuse shape

Square body, knife blade contacts

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type T Indicator for micro

Construction size

3

Packaging type

Standard

Voltage rating

690 V (IEC)

Fuse type

DIN 43620

T indicator for micro

Bladed

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)