



## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

### Amperage Rating

1250 A

### Breaking capacity

200 kA

### Fuse indicator

Centre fuse status indicator

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC

### Fuse size

3

### Rated voltage AC

690 V

### Center-to-center distance of connections

108 mm

### Current type

AC

### Mounting dimension

M10

### Class

Class aR

### Clearing (I<sub>2</sub>T)

1950000 at 660 V

### Watt losses

140 W

### Clearing loss

140

## Resources

### Catalogs

170M6266-Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

### Technical data sheets

720014 DIN 43653 690V

#### Fuse shape

Square body, slotted center bolted tags

#### Pre arc (I2T)

460000

#### Color

None

#### Interrupt rating

200 kAIC

#### Connection

Blade end x blade end

#### Construction size

3

#### Packaging type

Standard

#### Voltage rating

690 V (IEC), 700 V (UL)

#### Fuse type

DIN 43653

KN/110 Type K Indicator for Micro

#### Fuse system (according to IEC 60269)

Other



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)