

Eaton 170M6415

Catalog Number: 170M6415

Fuse-link, high speed, 1100 A, AC 690 V, size 3, aR, IEC, UL, single indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M6415
	UPC
	051712264136
EAN	Product Length/Depth
5027590462105	53 mm
Product Height	Product Width
76 mm	76 mm
Product Weight	Warranty
825 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

1100 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

3

Rated voltage AC

690 V

Center-to-center distance of connections

52 mm

Current type

AC

Mounting dimension

M12

Class

Class aR

Clearing (I₂T)

130000 at 660 V

Watt losses

130 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[170M6415~FUUSE 1100A 690V 3BN/50 AR UC](#)

[Bussmann series complete full line catalog no. 1007](#)

Pre arc (I2T)

190000

Color

None

Interrupt rating

200 kAIC

Construction size

3

Mounting method

Flush

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

Flush end

B/Visual indicator

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia