

# Eaton 170M6463

Catalog Number: 170M6463

Fuse-link, high speed, 900 A, AC 690 V, size 3, aR, IEC, UL, type K indicator

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed square body fuse	170M6463
	<b>UPC</b>
	051712809672
<b>EAN</b>	<b>Product Length/Depth</b>
5027590462594	168 mm
<b>Product Height</b>	<b>Product Width</b>
76 mm	95 mm
<b>Product Weight</b>	<b>Warranty</b>
845 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

### Amperage Rating

900 A

### Breaking capacity

200 kA

### Fuse indicator

Centre fuse status indicator

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC

### Fuse size

3

### Rated voltage AC

690 V

### Center-to-center distance of connections

52.4 mm

### Current type

AC

### Mounting dimension

M12

### Class

Class aR

### Clearing (I<sup>2</sup>T)

670000 at 660 V

### Watt losses

120 W

### Fuse shape

Square body, flush end contacts

## Resources

### Catalogs

Bussmann series complete full line catalog no. 1007

170M6463-Eaton Bussmann series high speed square body fuse

Pre arc (I2T)

100000

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type K Indicator for micro

Construction size

3

Mounting method

Flush

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

Flush end

BKN/Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)