

Eaton 170M6500

Catalog Number: 170M6500

Fuse-link, high speed, 1250 A, AC 1100 V, size 3, 76 x 92 x 83 mm, aR, IEC, UL, type K indicator

General specifications



Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M6500
	UPC
	051712264303
EAN	Product Length/Depth
5996516019566	168 mm
Product Height	Product Width
76 mm	95 mm
Product Weight	Warranty
1358 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

1250 A

Breaking capacity

100 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

3

Rated voltage AC

1100 V

Center-to-center distance of connections

91.4 mm

Current type

AC

Mounting dimension

M12

Class

Class aR

Clearing (I2T)

3950000 at 1000 V

Watt losses

145 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

170M6500-Eaton Bussmann series high speed square body fuse

mCAD model

U0773R.stp

Pre arc (I2T)

810000

Color

None

Interrupt rating

100 kAIC

Fitted with:

Type K Indicator for micro

Construction size

3

Mounting method

Flush

Packaging type

Standard

Voltage rating

1100 V

Fuse type

Flush end

BKN/90 Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)