
Eaton 170M6548

Catalog Number: 170M6548

Fuse-link, high speed, 1000 A, AC 1100 V, size 3, 76 x 92 x 83 mm, aR, IEC, UL, single indicator





Eaton Bussmann series high speed

square body fuse

EAN

5996516019788

Product Height

76 mm

Product Weight

1338 g

Compliances

CE Marked RoHS Compliant Catalog Number

170M6548

UPC

051712264525

Product Length/Depth

168 mm

Product Width

95 mm

Warranty

Not Applicable

Certifications

IEC Rated

UL Recognized



default Taxonomy Attribute Label

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 1000 A Breaking capacity 100 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 3 Rated voltage AC 1100 V Center-to-center distance of connections 82.4 mm Current type AC Mounting dimension M12 Class Class aR Clearing (I2T) 2150000 at 1000 V, 2750000 at 1250 V Watt losses 135 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

170M6548~Eaton Bussmann series high speed square body fuse

Compliance information

UKCA Fuse-links for the protection of semiconductor devices, Size 3

CE Fuse-links for the protection of semiconductor devices, Size 3

Pre arc (I2T)

450000

Color

None

Interrupt rating

100 kAIC

Fitted with:

Type K Indicator for micro

Construction size

3

Mounting method

Flush

Packaging type

Standard

Voltage rating

1100 V

Fuse type

Flush end

BKN/80 Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia