
Eaton 170M6549

Catalog Number: 170M6549

Fuse-link, high speed, 1100 A, AC 1000 V, size 3, aR, IEC, UL, type K indicator





Eaton Bussmann series high speed square body fuse

UPC

051712264532

Product Length/Depth

138 mm

Product Width

58 mm

Warranty

Not Applicable

Certifications

IEC Rated

UL Recognized

Catalog Number

170M6549

Model Code

FUSE 1100A 1000V 3BKN/80 AR

EAN

5996516019795

Product Height

45 mm

Product Weight

1264 g

Compliances

CE Marked

RoHS Compliant



default Taxonomy Attribute Label

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 1100 A Breaking capacity 100 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Fuse size 3 Rated voltage AC 1000 V Center-to-center distance of connections 82.4 mm Current type AC Mounting dimension M12 Class Class aR Clearing (I2T) 2800000 at 1000 V, 3600000 at 1250 V Watt losses 140 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

170M6549~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Compliance information

CE Fuse-links for the protection of semiconductor devices, Size 3

UKCA Fuse-links for the protection of semiconductor devices, Size 3

Pre arc (I2T)

575000

Color

None

Interrupt rating

100 kAIC

Fitted with:

Type K Indicator for micro

Construction size

3

Mounting method

Flush

Packaging type

Standard

Voltage rating

1000 V (IEC)

Fuse type

Flush end

BKN/80 Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia