



## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

### Amperage Rating

1000 A

### Breaking capacity

200 kA

### Fuse indicator

Centre fuse status indicator

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC

### Fuse size

3

### Rated voltage AC

690 V

### Center-to-center distance of connections

91 mm

### Current type

AC

### Mounting dimension

Other

### Class

Class aR

### Clearing (I2T)

945000 at 660 V

### Watt losses

122 W

### Fuse shape

Square body, center bolted tags

## Resources

### Catalogs

170M6664-Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Pre arc (I2T)

140000

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type K Indicator for micro

Connection

Blade end x blade end

Construction size

3

Packaging type

Standard

Voltage rating

690 V

Fuse type

US Style

FKE/Type K indicator for micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)