Eaton 170M6665

Catalog Number: 170M6665

Fuse-link, high speed, 1100 A, AC 690 V, size 3, 76 x 92 x 135 mm, aR, IEC, UL, single indicator

General specifications



Eaton Bussmann series high speed

square body fuse

Catalog Number

170M6665

UPC

051712265041

Product Length/Depth

EAN

5996516020326

Product Height

76 mm

Product Width

95 mm

168 mm

Product Weight

983 g

Warranty

Not Applicable

Compliances

CE Marked RoHS Compliant Certifications

UL Recognized IEC Rated



default Taxonomy Attribute LabelType Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 1100 A Breaking capacity 200 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 3 Rated voltage AC 690 V Center-to-center distance of connections 91 mm Current type AC Mounting dimension Other Class Class aR Clearing (I2T) 1300000 at 660 V Watt losses 130 W

Fuse shape

Square body, center bolted tags

Resources

Catalogs

170M6665~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Pre arc (I2T)

190000

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type K Indicator for micro

Connection

Blade end x blade end

Construction size

3

Packaging type

Standard

Voltage rating

690 V

Fuse type

US Style

FKE/Type K indicator for micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia