# Eaton 170M6761

### Catalog Number: 170M6761

Fuse-link, high speed, 700 A, AC 690 V, size 3, 76 x 92 x 139 mm, aR, IEC, UL, single indicator

#### General specifications

**Product Name** 

Eaton Bussmann series high speed square body fuse

Catalog Number 170M6761

UPC

051712265522

EAN

5996516020678

**Product Weight** 

**Product Height** 

76 mm

986 g

168 mm

Product Length/Depth

**Product Width** 95 mm

Warranty

Not Applicable

Certifications

**IEC Rated** 

**UL** Recognized

Photo is representative





#### default Taxonomy Attribute Label

## Type Fuse Application semiconductor protection Amperage Rating 700 A Breaking capacity 200 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 3 Rated voltage AC 690 V Center-to-center distance of connections 114 mm Current type AC Mounting dimension Other Class Class aR Clearing (I2T) 300000 at 660 V Watt losses 110 W Fuse shape Square body, center bolted tags

Pre arc (I2T)

#### Resources

#### Catalogs

170M6761~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

44500

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type K Indicator for micro

Connection

Blade end x blade end

Construction size

3

Packaging type

Standard

Voltage rating

690 V

Fuse type

US Style

FKE/115 Type K indicator for micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia