# Eaton 170M8623

### Catalog Number: 170M8623

Fuse-link, high speed, 900 A, AC 1000 V, DIN 3,  $74 \times 92 \times 138$  mm, aR, DIN, IEC, single indicator

### General specifications



Eaton Bussmann series high speed square body fuse

UPC

051712604260

Product Length/Depth

141 mm

**Product Width** 

82.5 mm

Warranty

Not Applicable

Certifications

IEC Rated
UL Recognized

Catalog Number

170M8623

Model Code

FUSE 900A 1000V 3KN/110 AR UR

**EAN** 

5996516022535

Product Height

76 mm

**Product Weight** 

1305 g

Compliances

CE Marked RoHS Compliant

Photo is representative



## default Taxonomy Attribute LabelType Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 900 A Breaking capacity 125 kA Fuse indicator Centre fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC Fuse size 3 Rated voltage AC 1000 V Center-to-center distance of connections 108 mm Current type AC Mounting dimension M10 Class Class aR Clearing (I2T) 150000 at 1000 V Watt losses

145 W

Fuse shape

Square body, slotted center bolted tags

### Resources

#### Catalogs

170M8623~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

### Compliance information

UKCA Fuse-links for the protection of semiconductor devices, Size 3

CE Fuse-links for the protection of semiconductor devices, Size 3

### Pre arc (I2T)

250000

Color

None

Interrupt rating

125 kAIC

Construction size

3

Packaging type

Standard

Voltage rating

1000 V (IEC)

Fuse type

DIN 43653

KN/110 Type K Indicator for Micro

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia