

Eaton 170M8635

Catalog Number: 170M8635

Fuse-link, high speed, 630 A, AC 1000 V, DIN 3, 74 x 90 x 139 mm, aR, DIN, IEC, single indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M8635
	UPC
	051712604376
EAN	Product Length/Depth
5996516022603	141 mm
Product Height	Product Width
76 mm	82.5 mm
Product Weight	Warranty
1275 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

630 A

Breaking capacity

125 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

3

Rated voltage AC

1000 V

Center-to-center distance of connections

108 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I²T)

490000 at 1000 V

Watt losses

120 W

Fuse shape

Square body, slotted center bolted tags

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[170M8635-Eaton Bussmann series high speed square body fuse](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE Fuse-links for the protection of semiconductor devices, Size 3](#)

[UKCA Fuse-links for the protection of semiconductor devices, Size 3](#)

Pre arc (I2T)

82500

Color

None

Interrupt rating

125 kAIC

Construction size

3

Packaging type

Standard

Voltage rating

1000 V (IEC)

Fuse type

DIN 43653

TN/110 Type T Indicator for Micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia