

Eaton 180MMT

Catalog Number: 180MMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 180A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

General specifications



Photo is representative

Product Name

Eaton Bussmann series high speed
british standard fuse

Catalog Number

180MMT

UPC

051712832090

EAN

5027590036269

Product Length/Depth

98 mm

Product Height

40 mm

Product Width

97 mm

Product Weight

478 g

Warranty

Not Applicable

Compliances

CE Marked
RoHS Compliant

Certifications

IEC Rated
UL Recognized
Designed and tested to BS88 part 4
IEC 60269-4
UL recognized

Electrical data

Amperage Rating

180 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

1650

Clearing (I2T)

12000

Watt losses

42 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Certification reports

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Technical data sheets

[720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses](#)