Eaton 200LMT

Catalog Number: 200LMT

Eaton Bussmann series high speed British standard fuse, Single barrel, 200A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 150 VDC (IEC). 50 kA at 150 VDC (UL)

General specifications

Product Name

Eaton Bussmann series high speed british standard fuse

UPC

051712832205

Product Height

41 mm

Product Weight 185 g

Certifications

IEC Rated UL Recognized Designed and tested to BS88 part 4 UL recognized IEC 60269-4 CCC Catalog Number 200LMT

5027590037006

Product Length/Depth

84 mm

EAN

Product Width

39 mm

Compliances

CE Marked RoHS Compliant





Electrical data

Amperage Rating

200 A

Voltage rating 240 Vac, 150 Vdc

Rated voltage AC

240 V

Rated voltage DC

150 V

Interrupt rating

200 kA RMS Sym, 40 kA at 150 Vdc (IEC) 200 kA RMS Sym, 50 kA at 150 Vdc (UL)

Class

Class aR

Pre arc (I2T)

1500

Clearing (I2T)

20000

Watt losses

28 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-250 Trip indicator kit (indicator + clips) TI250 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

Resources

Brochures

eaton-bussmann-series-bs88-high-speed-fuses-product-aidpa135003en-us.pdf

Catalogues IEC high speed fuse links

Certification reports DA-DC-00004682

DA-DC-00004685

Technical data sheets 720004 LCT, LET, LMMT, LMT



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia