

Eaton 20CT

Catalog Number: 20CT

Eaton Bussmann series high speed British standard fuse, 20A, 200 kAIC, None, Fuse, Blade end X blade end, Stud



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	20CT
	Packing Unit
	Case Pack Pack
EAN	Quantity
5027590344364	1680
5027590036610	20
Gross Weight	Length
17.096 kg	385 mm
0.172 kg	82 mm
Width	Height
280 mm	175 mm
90 mm	21 mm
Volume	ERP Name
18865 cm ³	SAP-UNITY
154.98 cm ³	SAP-UNITY
Product Length/Depth	Product Height
73 mm	9 mm
Product Width	Product Weight
9 mm	8.6 g
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized
	Designed and tested to BS88 part 4
	IEC 60269-4

Electrical data

Amperage Rating

20 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

500 V

Interrupt rating

90 kA RMS Sym, 40 kA at 500 Vdc (IEC)
200 kA RMS Sym, 50 kA at 500 Vdc (UL)

Class

Class aR

Pre arc (I2T)

32

Clearing (I2T)

150

Watt losses

7 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

Non Indicating

Compatible Trip indicator/Microswitch

Suitable for

TI700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogs

[IEC high speed fuse links](#)

Certification reports

[DA-DC-00004685](#)
[DA-DC-00004682](#)

Technical data sheets

[720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses](#)