Eaton 250MT

Catalog Number: 250MT

Eaton Bussmann series high speed British standard fuse, Single barrel, 250A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

General specifications



Eaton Bussmann series high speed

british standard fuse

5027590039321

Product Height

39 mm

EAN

Product Weight

236 g

Compliances
CE Marked

RoHS Compliant

Catalog Number

250MT

UPC

051712833080

Product Length/Depth

110 mm

Product Width

39 mm

Warranty

Not Applicable

Certifications

UL Recognized IEC Rated

Designed and tested to BS88 part 4 IEC 60269-4

UL recognized





Electrical data

Amperage Rating

250 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

11500

Clearing (I2T)

80000 at 415 V, 110000 at 660 V

Watt losses

32 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

eaton-bussmann-series-bs88-high-speed-fuses-product-aidpal35003en-us.pdf

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports

DA-DC-00004682

DA-DC-00004685

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.







