

Eaton 25LET

Catalog Number: 25LET

Eaton Bussmann series high speed British standard fuse, 25A, 280 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	25LET
	EAN
	5027590470896
UPC	Product Length/Depth
051712833233	55 mm
Product Height	Product Width
18 mm	18 mm
Product Weight	Compliances
32 g	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	
Designed and tested to BS88 part 4	
IEC 60269-4	

Electrical data

Amperage Rating

25 A

Voltage rating

280 V

Rated voltage AC

280 V

Rated voltage DC

150 V

Interrupt rating

200 kA RMS Sym, 50 kA DC at 150 Vdc

Class

Class aR

Pre arc (I2T)

18

Clearing (I2T)

250

Watt losses

4 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

TI500 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogues

[IEC high speed fuse links](#)

Certification reports

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Technical data sheets

[720004 LCT, LET, LMMT, LMT](#)