Eaton 280FM

Catalog Number: 280FM

Eaton Bussmann series high speed British standard fuse, Single barrel, 280A, 690 VAC/450 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 450 VDC (IEC), 50 kA at 500 VDC (UL)

General specifications

Product Name

Eaton Bussmann series high speed british standard fuse

EAN

5027590039598

Product Height 45 mm

Product Weight 226 g

Compliances CE Marked RoHS Compliant UPC 051712833387

Catalog Number

280FM

Product Length/Depth 46 mm

Product Width 115 mm

Warranty Not Applicable

Certifications

UL Recognized IEC Rated Designed and tested to BS88 part 4 IEC 60269-4 UL recognized CCC





Electrical data

Amperage Rating

280 A

Voltage rating 690 V (IEC), 700 V (UL)

Rated voltage AC 690 V

.....

Rated voltage DC 450 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 450 Vdc (IEC), 50 kA at 500 Vdc (UL)

Class

Class aR

Pre arc (I2T)

7000

Clearing (I2T) 30500 at 415 V, 55000 at 660 V

Watt losses

48 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-600 Trip indicator kit (indicator + clips) TI700 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

Resources

Brochures

eaton-bussmann-series-bs88-high-speed-fuses-product-aidpa135003en-us.pdf

Catalogs IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports DA-DC-00004685

DA-DC-00004682

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia