

Eaton 280MMT

Catalog Number: 280MMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 280A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	280MMT
	UPC
	051712833394
EAN	Product Length/Depth
5027590039604	110 mm
Product Height	Product Width
83 mm	39 mm
Product Weight	Warranty
478 g	Not Applicable
Compliances	
RoHS Compliant	
CE Marked	

Electrical data

Amperage Rating

280 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

6600

Clearing (I2T)

47000

Watt losses

47 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Certification reports

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Technical data sheets

[720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses](#)