Eaton 315FM

Catalog Number: 315FM

Eaton Bussmann series high speed British standard fuse, Single barrel, 315A, 690 VAC/450 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 450 VDC (IEC), 50 kA at 500 VDC (UL)

General specifications

Product Name

Eaton Bussmann series high speed british standard fuse

EAN

5027590043427

Product Height 39 mm

Product Weight 234 g

Compliances CE Marked RoHS Compliant

315FM UPC

051712833806

Catalog Number

Product Length/Depth

112 mm

Product Width 39 mm

Warranty Not Applicable

Certifications

UL Recognized IEC Rated Designed and tested to BS88 part 4 IEC 60269-4 UL recognized CCC





Electrical data

Amperage Rating

315 A

Voltage rating 690 V (IEC), 700 V (UL)

Rated voltage AC 690 V

- - -

Rated voltage DC 450 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 450 Vdc (IEC), 50 kA at 500 Vdc (UL)

Class

Class aR

Pre arc (I2T)

10000

Clearing (I2T) 40000 at 415 V, 77000 at 660 V

Watt losses

55 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-600 Trip indicator kit (indicator + clips) TI700 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

Resources

Brochures

eaton-bussmann-series-bs88-high-speed-fuses-product-aidpa135003en-us.pdf

Catalogs IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports DA-DC-00004682

DA-DC-00004685

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia