

Eaton 315NHM2B-690

Catalog Number: 315NHM2B-690

Fuse-link, LV, 315 A, AC 690 V, NH2, aM, IEC, dual indicator, live gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	315NHM2B-690
	UPC
	051712419864
EAN	Product Length/Depth
5027590476553	150 mm
Product Height	Product Width
71 mm	54 mm
Product Weight	Compliances
760 g	CE Marked
	RoHS Compliant
Certifications	
IEC 60269-1	
IEC 60269-2	
DIN 43620	

Electrical data

Amperage Rating

315 A

Voltage rating

690 V

Voltage type

AC

Breaking capacity

120 kA

Class

Class aM

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH2

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Resources

Catalogs

CA134002EN

NH Fuse links, bases and gear

Compliance information

UKCA 690V NH Motor rated

CE 690V NH Motor rated

Multimedia

Eaton Bussmann – NH fuse link portfolio

Presentations

NH Overview Video

Technical data sheets

10165 NH 500 and 690 Volts aM

Technical service bulletins

Datasheet - 315NHM2B-690



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)