

Eaton 315NHM3B-690

Catalog Number: 315NHM3B-690

Eaton Fuse-link, LV, 315 A, AC 690 V, NH3, aM, IEC, dual indicator, live gripping lugs



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	315NHM3B-690
	EAN
	5027590476577
Product Length/Depth	Product Height
150 mm	86 mm
Product Width	Product Weight
72 mm	1139.33 g
Compliances	Certifications
CE Marked	IEC 60269-1
RoHS Compliant	IEC 60269-2
	DIN 43620

defaultTaxonomyAttributeLabel

Type

Fuse

Application

industrial

Amperage Rating

315 A

Fitted with:

Metal gripping lugs

Fuse size

NH3

Current type

AC

Breaking capacity

120 kA

Rated switching capacity

120 kA

Rated voltage AC

690 V

Class

Class aM

Fuse type

Square body with knife blade contact

Accessory/spare part type

SDL-3 Solid link

FEH- Fuse extraction handle

SD3-SK Shroud kit

SD3-PB 2-phase barriers and 2 ganging links

TD3-IP20 Triple pole protection kit

Utilization category

aM (switchgear protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Resources

Catalogs

CA134002EN

NH Fuse links, bases and gear

Compliance information

CE 690V NH Motor rated

UKCA 690V NH Motor rated

Multimedia

Eaton Bussmann – NH fuse link portfolio

Presentations

NH Overview Video

Technical data sheets

10165 NH 500 and 690 Volts aM

Technical service bulletins

Datasheet - 315NHM3B-690

Watt losses

20 W

Connection

Blade end

Construction

NH3

Construction size

NH3

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

SD3-D Single pole NH Fuse base

TD3-D Tripe pole NH Fuse base

Microswitch 170H0235

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

690 V

Rated switching capacity AC

120 kA