Eaton 350FM

Catalog Number: 350FM

Eaton Bussmann series high speed British standard fuse, Single barrel, 350A, 690 VAC/450 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 450 VDC (IEC), 50 kA at 500 VDC (UL)

General specifications



Eaton Bussmann series high speed

british standard fuse

5027590044783

Product Height

39 mm

EAN

Product Weight

234 g

Compliances

CE Marked RoHS Compliant Catalog Number

350FM

UPC

051712834063

Product Length/Depth

112 mm

Product Width

39 mm

Warranty

Not Applicable

Certifications

IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4 UL recognized

CCC





Electrical data

Amperage Rating

350 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

450 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 450 Vdc (IEC), 50 kA at 500 Vdc (UL)

Class

Class aR

Pre arc (I2T)

15000

Clearing (I2T)

60000 at 415 V, 105000 at 660 V

Watt losses

55 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

 $eaton-bus smann-series-bs 88-high-speed-fuses-product-aid-\\pal 35003 en-us.pdf$

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports

DA-DC-00004685

DA-DC-00004682

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia