

Eaton 355LMT

Catalog Number: 355LMT

Eaton Bussmann series high speed British standard fuse, Single barrel, 355A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 150 VDC (IEC). 50 kA at 150 VDC (UL)



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	355LMT
	EAN
	5027590044844
UPC	Product Length/Depth
051712834100	84 mm
Product Height	Product Width
41 mm	39 mm
Product Weight	Compliances
185 g	CE Marked
	RoHS Compliant
Certifications	
UL Recognized	
IEC Rated	
Designed and tested to BS88 part 4	
UL recognized	
IEC 60269-4	
CCC	

Electrical data

Amperage Rating

355 A

Voltage rating

240 Vac, 150 Vdc

Rated voltage AC

240 V

Rated voltage DC

150 V

Interrupt rating

200 kA RMS Sym, 40 kA at 150 Vdc (IEC)

200 kA RMS Sym, 50 kA at 150 Vdc (UL)

Class

Class aR

Pre arc (I2T)

8000

Clearing (I2T)

100000

Watt losses

35 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-250 Trip indicator kit (indicator + clips)

TI250 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogues

[IEC high speed fuse links](#)

Certification reports

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Technical data sheets

[720004 LCT, LET, LMMT, LMT](#)