

Eaton 355MMT

Catalog Number: 355MMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 355A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	355MMT
	UPC
	051712834117
EAN	Product Length/Depth
5027590044868	110 mm
Product Height	Product Width
83 mm	39 mm
Product Weight	Warranty
465 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized
	Designed and tested to BS88 part 4
	IEC 60269-4
	UL recognized

Electrical data

Amperage Rating

355 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

8600

Clearing (I2T)

97000

Watt losses

54 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Certification reports

[DA-DC-00004682](#)

[DA-DC-00004685](#)

Technical data sheets

[720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses](#)