# Eaton 355MT

# Catalog Number: 355MT

Eaton Bussmann series high speed British standard fuse, Single barrel, 355A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

## General specifications



Eaton Bussmann series high speed

british standard fuse

EAN

5027590044882

**Product Height** 

45 mm

**Product Weight** 

236 g

Compliances

RoHS Compliant

CE Marked

Catalog Number

355MT

UPC

051712834124

Product Length/Depth

46 mm

**Product Width** 

115 mm

Warranty

Not Applicable

Certifications

UL Recognized

IEC Rated

Designed and tested to BS88 part 4

IEC 60269-4 UL recognized





#### Electrical data

Amperage Rating

355 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

22000

Clearing (I2T)

160000 at 415 V, 200000 at 660 V

Watt losses

51 W

#### **Product specifications**

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

### Compatble Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

#### Resources

eaton-bussmann-series-bs88-high-speed-fuses-product-aidpal35003en-us.pdf

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports

DA-DC-00004682

DA-DC-00004685

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.







