

Eaton 355NHM2B-690

Catalog Number: 355NHM2B-690

Fuse-link, LV, 355 A, AC 690 V, NH2, aM, IEC, dual indicator, live gripping lugs

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	355NHM2B-690
	Model Code
	NH FUSE 355A 690V aM SIZE 2
UPC	EAN
051712419871	5027590477574
Product Length/Depth	Product Height
150 mm	71 mm
Product Width	Product Weight
54 mm	659 g
Warranty	Compliances
Not Applicable	RoHS Compliant CE Marked
Certifications	
IEC 60269-1 IEC 60269-2 DIN 43620	



defaultTaxonomyAttributeLabel

Type

Fuse

Application

industrial

Amperage Rating

355 A

Fitted with:

Metal gripping lugs

Fuse size

NH2

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

690 V

Class

Class aM

Fuse type

Square body with knife blade contact

Accessory/spare part type

SDL-2 Solid link

FEH- Fuse extraction handle

SD12-SK Shroud kit

SD12-PB 2-phase barriers and 2 ganging links

TD2-IP20 Triple pole protection kit

Utilization category

aM (switchgear protection)

Interrupt rating

120 kAIC

Resources

Catalogs

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[NH Fuse links, bases and gear](#)

[CA134002EN](#)

[Bussmann series complete full line catalog no. 1007](#)

Compliance information

[CE 690V NH Motor rated](#)

[UKCA 690V NH Motor rated](#)

Multimedia

[Eaton Bussmann – NH fuse link portfolio](#)

Presentations

[NH Overview Video](#)

Technical data sheets

[10165 NH 500 and 690 Volts aM](#)

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Watt losses

28 W

Connection

Blade end

Construction

NH2

Construction size

NH2

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Material

Ceramic body

Packaging type

Standard

Quantity

3

Voltage rating

690 V

Rated switching capacity AC

120 kA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)