# Eaton 35LET

# Catalog Number: 35LET

Eaton Bussmann series high speed British standard fuse, 35A, 280 VAC/150 VDC (UL), Class aR, 200 kA RMS Sym., Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC

## General specifications



Eaton Bussmann series high speed

british standard fuse

UPC

051712834223

**Product Height** 

18 mm

**Product Weight** 

31.3 g

Catalog Number

35LET

EAN

5027590477772

Product Length/Depth

55 mm

**Product Width** 

18 mm

Compliances

**CE Marked** 

RoHS Compliant

#### Certifications

IEC Rated

**UL** Recognized

Designed and tested to BS88 part 4

IEC 60269-4





#### Electrical data

Amperage Rating

35 A

Voltage rating

280 V

Rated voltage AC

280 V

Rated voltage DC

150 V

Interrupt rating

200 kA RMS Sym, 50 kA DC at 150 Vdc

Class

Class aR

Pre arc (I2T)

35

Clearing (I2T)

600

Watt losses

5 W

### **Product specifications**

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

# Compatble Trip indicator/Microswitch

Suitable for

TI500 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor

#### Resources

**Brochures** 

eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf

Catalogues

IEC high speed fuse links

Certification reports

DA-DC-00004685

DA-DC-00004682

Technical data sheets

720004 LCT, LET, LMMT, LMT



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.









Eaton.com/socialmedia