Eaton 400LMMT

Catalog Number: 400LMMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 400A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 150 VDC (IEC). 50 kA at 150 VDC (UL)

General specifications



Product Name

Eaton Bussmann series high speed

british standard fuse

400LMMT

Catalog Number

Packing Unit

Case Pack

Quantity

5027590357111 36

Gross Weight

13.032 kg

Length

385 mm

Width

EAN

280 mm

Height

175 mm

Volume

Ime ERP Name

18865 cm³ SAP-UNITY

Product Length/Depth

Product Height 39 mm

82 mm

Product Weight

Product Width

362 g

91 mm

00**–** 9

Compliances

Certifications
UL Recognized

CE Marked

IEC Rated

RoHS Compliant

Designed and tested to BS88 part 4

UL recognized



CCC

Electrical data

Amperage Rating

400 A

Voltage rating

240 Vac, 150 Vdc

Rated voltage AC

240 V

Rated voltage DC

150 V

Interrupt rating

200 kA RMS Sym, 40 kA at 150 Vdc (IEC) 200 kA RMS Sym, 50 kA at 150 Vdc (UL)

Class

Class aR

Pre arc (I2T)

600

Clearing (I2T)

35000

Watt losses

60 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-250 Trip indicator kit (indicator + clips)

TI250 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

 $eaton-bus smann-series-bs 88-high-speed-fuses-product-aid-\\pal 35003 en-us.pdf$

Catalogs

IEC high speed fuse links

Certification reports

DA-DC-00004685

DA-DC-00004682

Technical data sheets

720004 LCT, LET, LMMT, LMT



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia