
Eaton 400LMT

Catalog Number: 400LMT

Eaton Bussmann series high speed British standard fuse, Single barrel, 400A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 150 VDC (IEC). 50 kA at 150 VDC (UL)





Eaton Bussmann series high speed

british standard fuse

Product Height

30 mm

Product Weight

185 g

Catalog Number

400LMT

Product Length/Depth

52 mm

Product Width

126 mm

Compliances

CE Marked

RoHS Compliant

Certifications

UL Recognized

IEC Rated

Designed and tested to BS88 part 4

UL recognized

IEC 60269-4

CCC



EATON®

Electrical data

Amperage Rating

400 A

Voltage rating

240 Vac, 150 Vdc

Rated voltage AC

240 V

Rated voltage DC

150 V

Interrupt rating

200 kA RMS Sym, 40 kA at 150 Vdc (IEC) 200 kA RMS Sym, 50 kA at 150 Vdc (UL)

Class

Class aR

Pre arc (I2T)

1400

Clearing (I2T)

160000

Watt losses

40 W

Product specifications

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-250 Trip indicator kit (indicator + clips)

TI250 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

eaton-bussmann-series-bs88-high-speed-fuses-product-aidpal35003en-us.pdf

Catalogs

IEC high speed fuse links

Certification reports

DA-DC-00004682

DA-DC-00004685

Technical data sheets

720004 LCT, LET, LMMT, LMT



Eaton Corporation plc **Eaton House** 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia