# Eaton 400MMT

# Catalog Number: 400MMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 400A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

# General specifications



Eaton Bussmann series high speed

british standard fuse

EAN

5027590046879

**Product Height** 

83 mm

**Product Weight** 

450 g

Compliances **CE Marked** 

**RoHS Compliant** 

Catalog Number

400MMT

**UPC** 

051712834940

Product Length/Depth

110 mm

**Product Width** 

39 mm

Warranty

Not Applicable

Certifications

**IEC Rated** 

**UL** Recognized

Designed and tested to BS88 part 4

IEC 60269-4

UL recognized



#### Electrical data

Amperage Rating

400 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

21000

Clearing (I2T)

150000

Watt losses

60 W

### **Product specifications**

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

## Compatble Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

#### Resources

eaton-bussmann-series-bs88-high-speed-fuses-product-aidpal35003en-us.pdf

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports

DA-DC-00004682

DA-DC-00004685

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.







