

Eaton 400NHG3B-690

Catalog Number: 400NHG3B-690

Eaton Bussmann series low voltage NH Fuse, Live gripping lug, 690V, 400A, 120 kAIC, Combination fuse status indicator, fuse, Blade end connection, Class C gL/gG, Square-body with knife blade contact, Ceramic body



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage NH Fuse	400NHG3B-690
	Model Code
	NH FUSE 400A 690V gG SIZE 3
UPC	EAN
051712193085	5027590479844
Product Length/Depth	Product Height
150 mm	86 mm
Product Width	Product Weight
71 mm	1.027 kg
Warranty	Compliances
Not Applicable	RoHS Compliant CE Marked
Certifications	
IEC 60269-1 IEC 60269-2 DIN 43620	

Electrical data

Amperage Rating

400 A

Voltage rating

690 V

Voltage type

AC

Breaking capacity

120 kA

Class

Class gG/gL

Frequency rating - min

45 Hz

Frequency rating - max

62 Hz

Product specification

Fuse size

NH3

Insulated metal gripping lugs (IMGL)

No

Accessories

Suitable for

SD3-D Single pole NH Fuse base

TD3-D Tripe pole NH Fuse base

Microswitch 170H0235

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Resources

Catalogs

CA134002EN

NH Fuse links, bases and gear

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

Bussmann series complete full line catalog no. 1007

Compliance information

[UKCA NH Size 3, 690V fuse-links](#)

[CE NH Size 3, 690V fuse-link](#)

Multimedia

[Eaton Bussmann – NH fuse link portfolio](#)

Presentations

[NH Overview Video](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)