Eaton 45ET

Catalog Number: 45ET

Eaton Bussmann series high speed British standard fuse, Single barrel, 45A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 **VDC**

General specifications



Catalog Number

Eaton Bussmann series high speed

british standard fuse

45ET **Packing Unit**

Case Pack

Pack

EAN Quantity

5027590354097 480 5027590047609 10

Gross Weight

Length 20.456 kg 385 mm 0.414 kg 82 mm

Width Height

280 mm 175 mm 91 mm 39 mm

Volume **ERP Name**

18865 cm³ SAP-UNITY 291.018 cm³ SAP-UNITY

Product Length/Depth **Product Height**

20 mm 76 mm

Product Width Product Weight

20 mm 41.4 g





Certifications

CE Marked **UL** Recognized

Electrical data

Amperage Rating

45 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

500 V

Interrupt rating

200 kA RMS Sym, 50 kA at 500 Vdc

Class

Class aR

Pre arc (I2T)

103

Clearing (I2T)

680 at 415 V, 1100 at 660 V

Watt losses

11 W

Product specifications

Designed and tested to BS88 part 4

Application

IEC 60269-4

Semiconductor, DC Common bus, DC drives, power

converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

eaton-bussmann-series-bs88-high-speed-fuses-product-aid-

pal35003en-us.pdf

Catalogs

IEC high speed fuse links

Certification reports

DA-DC-00004682

DA-DC-00004685

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.







