Eaton 500LMMT

Catalog Number: 500LMMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 500A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 150 VDC (IEC). 50 kA at 150 VDC (UL)

General specifications



british standard fuse

Catalog Number

500LMMT

Packing Unit
Case Pack

EAN Quantity 5027590357203 36

Gross Weight Length
13.616 kg 385 mm

Width Height 280 mm 175 mm

Volume ERP Name 18865 cm³ SAP-UNITY

Product Length/Depth Product Height

84 mm 83 mm

Product Width Product Weight

38 mm 362 g

Compliances Certifications
CE Marked IEC Rated
RoHS Compliant UL Recognized

Designed and tested to BS88 part 4

UL recognized





CCC

Electrical data

Amperage Rating

500 A

Voltage rating

240 Vac, 150 Vdc

Rated voltage AC

240 V

Rated voltage DC

150 V

Interrupt rating

200 kA RMS Sym, 40 kA at 150 Vdc (IEC) 200 kA RMS Sym, 50 kA at 150 Vdc (UL)

Class

Class aR

Pre arc (I2T)

14000

Clearing (I2T)

80000

Watt losses

64 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

MC-250 Trip indicator kit (indicator + clips)

TI250 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

 $eaton-bus smann-series-bs 88-high-speed-fuses-product-aid-\\pal 35003 en-us.pdf$

Catalogs

IEC high speed fuse links

Certification reports

DA-DC-00004685

DA-DC-00004682

Technical data sheets

720004 LCT, LET, LMMT, LMT



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia